



**X-MILES**

UNLIMITED CHARGING

# XMT-EVC10

## EVSMART AC CHARGER



**GREEN ENERGY  
READILY AVAILABLE**

[WWW.XMILES.COM.MY](http://WWW.XMILES.COM.MY)



## KEY FEATURES AND BENEFITS



### **FITS OVER 99.5% OF POPULAR CAR MODELS**

Based on AI algorithm adaptive matching mainstream electric models, worry-free charging.



### **MULTI-SCENE INTELLIGENT CHARGING**

Plug and charge / RFID card / OCPP control three charging methods, independent authorization, not afraid of being stolen.



### **LEAN OPERATION MANAGEMENT OF VEHICLES, CHARGING STATIONS, AND PLATFORMS**

Compatible with 50+ CPO platforms in the world, OCPP 1.6J help you connect EV charger to the cloud, Cyber Security security.



### **SMART DYNAMIC LOAD BALANCING**

Intelligent adjustment of power output according to power grid load fluctuations, all-round protection of vehicles.



### **INTELLIGENT IOT DEVICE MONITORING**

Devices connect with WIFI & Bluetooth, real-time device monitoring via app, remote OTA updates.



# EVSmart AC Charging Specifications

## XMT-EVC10

### POWER

Input Rating	230V±10% (Single-Phase)	400V±10% (Three-Phase)
Output Current & Power	7kW (32A)	11kW (16A) / 22kW (32A)
Power Wiring	L / N / PE	L1 / L2 / L3 / N / PE
Input Cord	Hardwire	
Mains Frequency	50 / 60 Hz	
Connector Point	IEC 62196-2 Compliant, Type 2 with 5m cable / 7m (Optional)	
Ground Fault Detection	Built-in RCD (DC 6mA)	
Protection	UVP, OVP, RCD , SPD, Ground Fault Protection, OCP, OTP, Control Pilot Fault Protection	

### USER INTERFACE

Status Indication	LED Indication
Screen	4.3' Screen
Language	English
Connectivity	Bluetooth, Wi-Fi, Ethernet, 4G (Optional)
Communication Protocols	Compatible with multiple CPOs
Function Available	CT-Clamp
User Authentication	Plug & Charge, RFID Card, CPOs,
Card Reader	ISO 14443 A/B
Software Update	OTA

### CERTIFICATION & STANDARDS

Safety & Compliance	EN 62196-2:2017-06, EN IEC 61851-1:2019-10, EN IEC 61851-21-2:2021-09, EN 62196-1:2015-05, EN 61008-1 and IEC 62955
Certification	CE / CB
Warranty	36 Months

### GENERAL

Button	Emergency Button
Enclosure Rating	IK08; IP65 (cable)
Operating Altitude	< 2000m
Operating Temperature	-30°C ~ +50°C
Operating Humidity	5~95%
Mounting	Wall mount / Pedestal (Optional)
Colour	Silver
Product Dimensions (H x W x D)	351mm * 250mm * 130mm
Package Dimensions (H x W x D)	497mm * 348mm * 267mm





**X-MILES**

UNLIMITED CHARGING



**X MILES SDN. BHD.**

LOT 1793, JALAN KPB 4  
KAWASAN PERINDUSTRIAN  
KAMPUNG BARU BALAKONG  
43300 SERI KEMBANGAN  
SELANGOR DARUL EHSAN



+6014 364 1128



INFO@XMILES.COM.MY



[WWW.XMILES.COM.MY](http://WWW.XMILES.COM.MY)